


Required Tools

measuring
tape




drill with
2mm bit



phillips bit or
screwdriver



pencil



knife



Included Hardware

The hardware can be found in the small plastic bag included with your blind.



Installation Bracket
(inside window frame)



Installation Bracket
(outside window frame)



Remote Control



Screws for Wood,
Metal or Wall
Anchors



Wall Anchors for
Brick or Cement

Feedback?

Please write a review on our website letting us know your experience with Veneta Blinds

www.venetablinds.com.au

1 Installation Brackets

Installing inside the window frame...

- At top of window frame, measure 90mm in from each end and 40mm back from the front of the window frame, and mark the screw position for the small round hole on bracket.
- Place brackets in position and mark where the other screws will go.
- We recommend drilling pilot holes for the screws using a 2mm bit.
- Fix the brackets into position using 2 screws for each bracket.
- If more brackets are supplied, space them evenly between the first two brackets.



Installing outside the window frame...

- Measure 90mm in from top left and top right of where the blind will sit (normally edge of architrave) and mark the position of the centre of the brackets.
- Place brackets in position and mark where the other screws will go.
- We recommend using a spirit level to align brackets if not installing on the architrave.
- We recommend drilling pilot holes for the screws using a 2mm bit.
- Fix the brackets into position using 2 screws for each bracket.
- If more brackets are supplied, space them evenly between the first two brackets.

2 Install Blind

- Note the position of the bracket in the photo to the right...
- Position the second lip on top of the headrail into the front lip of bracket.
- Tilt the back of the blind up and apply firm pressure at the back of the blind, to click the blind into place.



3 Power Supply


- **240 Volt Rechargeable:** Plug the charger unit into the 240-volt wall socket and insert the connector into the end of the blind tube to charge. Charge time approx. 5-6 hours. Ensure you fully charge the motor for first use.
- **Battery Pack:** Position the battery pack in a suitable position and install the brackets using the screws provided.
- Place the battery pack into the clips and connect the battery tube to the blind.
- The remote is pre-programmed to the blind and ready to go.

Great Job... Enjoy your new Veneta Blinds!

Operating your Blind

- Use the remote to move the blinds up and down.
- Select left and right on the remote to change channels to operate a different blind.

Remote Control



- **Note: the remote control is already programmed to your blind and will work out of the box.**
- If, however you need to re-connect or set the limits, follow the instructions below...
- Connect Remote to Blind: Hold down the RED setting button at the end of the blind tube.
- The blind will move up and down slightly, then release button.
- On back of remote, press the 'C' button.
- The blind will move up and down slightly and is now connected to the motor.
- Reverse Direction of Blind: Hold both the 'L' button on the back of the remote and the 'STOP' button on the front of the remote at the same time.
- The blind will move up and down slightly and has now changed direction.
- Setting Bottom Limit: On the back of the remote, press and hold the 'L' button.
- The blind will move up and down slightly and then move up and down slightly again, now it is ready to set the limit and you can release the button.
- Press the 'DOWN' button on the remote.
- Allow the blind to run until you reach where you want to set the lower limit and press the 'STOP' button.
- On the back on the remote press the 'C' button.
- The blind will move up and down slightly.
- The lower limit is now set.
- Setting Upper Limit: Press the 'UP' button on the remote.
- Allow the blind to run until you reach where you want to set the upper limit and press the 'STOP' button.
- On the back of the remote press the 'C' button.
- The blind will now move up and down slightly.
- The upper limit is now set.

Maintaining your Blind

- Dusting: Dust can be removed using a feather duster or vacuum with brush attachment on low suction.
- Spot Cleaning: Use a warm damp cloth or a mild detergent for tougher stains.
- Dab the affected area, but do not rub the fabric. Finish with just a warm damp cloth.
- Allow the fabric to dry in the lowered position.